

FITTING INSTRUCTIONS

XK120 Spin-on kit

Partnumber: 017.210

This adaptor is intended for the above Jaguar models which are fitted with a Tecalemit F A2045 filter head. This number should be found on a brass plate rivetted to the filter head; if you cannot find this number check with your supplier that this is the correct item for your car.

Remove the bowl and the original filter. Remove the old seal for the filter bowl which will be embedded in a groove in the filter head; make sure that the groove is clean and contains no remains of the old seal or gasket sealant. Remove the snap-ring, and the splash plate (this looks like a large steel washer) in the centre of the filter head. If there is a felt washer under the plate remove this also.

There are two large diameter o-rings supplied with the kit; use the one which is the better fit in the in the outer groove of the filter head making sure that it is seated correctly. Place the long bolt through the bonded seal and through the small alloy washer, fit the small o-ring in the top of the filter head and then insert the bolt in the top of the filter head. Fit the medium-sized o-ring over the boss in the filter head (where the splash plate was fitted). Place the large alloy adaptor plate in position in the head and insert the special hollow bolt (complete with extension piece) up into the filter head to connect with the long bolt. Screw the two together tightly, but do not overtighten (Loctite is recommended here).

You are now ready to fit a spin-on filter to your Jaguar. We recommend our 011.050 filter. Fill the filter with oil before fitting and grease the filter's rubber sealing ring. Always check for oil leaks when starting the engine after replacing the filter. Renew the filter at the recommended intervals.

Also available for your Jaguar: braided stainless steel flexible brake and clutch hoses, fuel and oil lines, fuel filters and pumps, oil coolers etc. Ask for details.

